

SAVÁLLÓ HEGTOLDATOS GOLYÓSCSAP

hosszú, rövid B302

3-PC Butt Weld Ball Valve



Méret	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"
d	12,5	12,5	15	20	25	32	38	50	65	76	94
D	15,2	17,2	21,3	26,9	34,5	43,5	50	61,5	77	90	115
H	48	48	50	52	70	70	85	93	116	125	180
W	105	105	105	126	144	144	189	189	224	224	251
L	72	72	72	80	105	105	113	134	170	186	220
L1	225	225	225	225	256	256	260	275	334	345	365

1	Handle Sleeve	Plastic
2	Handle	SUS304
3	Gland Nut	SUS304
4	Stem Nut	SUS304
5	Spring Washer	SUS304
6	Packing	PTFE
7	Stem Seal	PTFE
8	Cap	CF8/CF8M
9	Bolt	SUS304
10	Nut	SUS304
11	Thrust Washer	SUS304
12	Body	CF8/CF8M
13	Ball Seat	RPTFE
14	Ball	CF8/CF8M
15	Stem	SUS304
16	Locking	SUS304

1000 PSI/PN63
 Full Port
 Investment Casting
 Blow-out Proof Stem
 Locking Device Handle
 PED97/23/EC
 AD2000-W0
 ASME B16.25 (Sch40)
 API598, EN12266

